

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

A-03075 FIGS. 1 - 24

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6

	TORQUE (kgf/cm)	θ_1	θ_d	θ_d/θ_1
CONDITION 1	1.6	45	30	2/3
CONDITION 2	1.3	45	20	4/9
CONDITION 3	1.2	45	18	2/5
CONDITION 4	1	45	15	1/3
CONDITION 5	0.7	45	10	2/9
CONDITION 6	1.8	30	30	1
CONDITION 7	1.7	30	25	5/6
CONDITION 8	1.3	30	18	3/5
CONDITION 9	1.1	30	12	2/5
CONDITION 10	0.9	30	8	4/15

FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13

r_1/r	STABILITY
1/1	X
1/2	X
1/3	O
1/4	O

FIG. 14




FIG. 15




FIG. 16.




FIG. 17

	GRANULARITY	D _v /D _n	CIRCULARITY
TONER 1	6.8	1.32	0.89
TONER 2	5.5	1.15	0.97
TONER 3	4.2	1.10	0.94
TONER 4	7.8	1.24	0.96
TONER 5	3.5	1.19	0.96
TONER 6	8.2	1.15	0.95

FIG. 18

	TOTAL AMOUNT (g)	AMOUNT OF SLEEVE (g)	METALLING MATERIAL	TONER	CARRIER	GRANULARITY	TONER SCATTERING	BACK- GROUND FOG	CARRIER DEPOSITION	CARRIER CHARGING
CONDITION 1	200	90	NONMAGNETIC	TONER 1	CARRIER 1	△	○	○	○	△
CONDITION 2	200	90	MAGNETIC	TONER 2	CARRIER 1	○	○	○	○	○
CONDITION 3	200	90	MAGNETIC	TONER 3	CARRIER 1	○	○	○	○	○
CONDITION 4	200	90	MAGNETIC	TONER 4	CARRIER 1	△	○	○	○	○
CONDITION 5	200	90	MAGNETIC	TONER 5	CARRIER 1	△	○	○	○	○
CONDITION 6	200	90	MAGNETIC	TONER 6	CARRIER 1	△	○	○	○	○
CONDITION 7	200	90	MAGNETIC	TONER 2	CARRIER 2	○	○	○	○	○
CONDITION 8	200	90	MAGNETIC	TONER 2	CARRIER 3	△	○	○	○	△
CONDITION 9	200	90	MAGNETIC	TONER 2	CARRIER 4	△	○	○	○	○
CONDITION 10	200	120	MAGNETIC	TONER 2	CARRIER 1	△	△	○	○	○
CONDITION 11	200	150	MAGNETIC	TONER 2	CARRIER 1	△	○	○	○	○
CONDITION 12	300	140	MAGNETIC	TONER 2	CARRIER 1	○	○	○	○	○
CONDITION 13	300	180	MAGNETIC	TONER 2	CARRIER 1	△	○	○	○	○
CONDITION 14	400	190	NONMAGNETIC	TONER 2	CARRIER 1	○	○	○	○	△
CONDITION 15	400	220	NONMAGNETIC	TONER 2	CARRIER 1	△	○	○	○	○

FIG. 19




FIG. 20

MEASUREMENT OF COATING RATIO
RATION FOR UNIT AREA




FIG. 21




FIG. 22

CARRIER GRAIN SIZE: 55 μm

	Gp (cm^3)	$\rho_c (\text{g}/\text{cm}^3)$	$\rho_r (\text{g}/\text{cm}^3)$	A (g/cm^2)	APPARENT COATING RATIO H	Gpxpr	CARRIER DEPOSITION	ROUGHNESS	SOLID IMAGE DENSITY	EMISSION AROUND SOLID	TONER SCATTERING
CONDITION 1	0.05	5.2	2.2	0.07	125	0.11	x	○	○	x	x
CONDITION 2	0.05	5.2	2.2	0.06	110	0.11	x	○	○	x	x
CONDITION 3	0.05	5.2	2.2	0.05	100	0.11	x	○	○	x	x
CONDITION 4	0.05	5.2	2.2	0.04	70	0.11	x	○	○	x	x
CONDITION 5	0.05	5.2	2.2	0.03	60	0.11	x	×	○	x	x
CONDITION 6	0.05	5.2	2.2	0.02	55	0.11	x	×	○	x	x
CONDITION 7	0.04	5.2	2.2	0.07	125	0.09	x	○	○	x	x
CONDITION 8	0.04	5.2	2.2	0.06	110	0.09	x	○	○	x	x
CONDITION 9	0.04	5.2	2.2	0.05	100	0.09	x	○	○	x	x
CONDITION 10	0.04	5.2	2.2	0.04	70	0.09	x	○	○	x	x
CONDITION 11	0.04	5.2	2.2	0.03	60	0.09	x	○	○	x	x
CONDITION 12	0.04	5.2	2.2	0.02	55	0.09	x	○	○	x	x
CONDITION 13	0.03	5.2	2.2	0.07	125	0.07	x	○	○	x	x
CONDITION 14	0.03	5.2	2.2	0.06	110	0.07	x	○	○	x	x
CONDITION 15	0.03	5.2	2.2	0.05	100	0.07	x	○	○	x	x
CONDITION 16	0.03	5.2	2.2	0.04	70	0.07	x	○	○	x	x
CONDITION 17	0.03	5.2	2.2	0.03	60	0.07	x	○	○	x	x
CONDITION 18	0.03	5.2	2.2	0.02	55	0.07	x	○	○	x	x
CONDITION 19	0.02	5.2	2.2	0.07	125	0.04	x	○	○	x	x
CONDITION 20	0.02	5.2	2.2	0.06	110	0.04	x	○	○	x	x
CONDITION 21	0.02	5.2	2.2	0.05	100	0.04	x	○	○	x	x
CONDITION 22	0.02	5.2	2.2	0.04	70	0.04	x	○	○	x	x
CONDITION 23	0.02	5.2	2.2	0.03	60	0.04	x	○	○	x	x
CONDITION 24	0.02	5.2	2.2	0.02	55	0.04	x	○	○	x	x

FIG. 23

CARRIER GRAIN SIZE: $35\mu\text{m}$

	ϵ_{P} (cm)	ρ_{C} (g/cm ³)	ρ_{T} (g/cm ³)	A(g/cm ²)	APPARENT COATING RATIO M	$\epsilon_{\text{P}} \times \epsilon_{\text{T}}$	CARRIER DEPOSITION	ROUGHNESS	SOLID IMAGE DENSITY	OMISION AROUND SIGHT	TOEER SCATTERING
CONDITION 1	0.05	5.2	1.8	0.07	140	0.09	x	o	x	x	x
CONDITION 2	0.05	5.2	1.8	0.06	130	0.09	o	o	x	x	x
CONDITION 3	0.05	5.2	1.8	0.05	120	0.09	o	o	x	x	x
CONDITION 4	0.05	5.2	1.8	0.04	100	0.08	o	o	x	x	x
CONDITION 5	0.05	5.2	1.8	0.03	90	0.08	o	o	x	x	x
CONDITION 6	0.05	5.2	1.8	0.02	80	0.09	o	o	x	x	x
CONDITION 7	0.04	5.2	1.8	0.07	140	0.07	x	x	x	x	x
CONDITION 8	0.04	5.2	1.8	0.06	130	0.07	x	x	x	x	x
CONDITION 9	0.04	5.2	1.8	0.05	120	0.07	x	x	x	x	x
CONDITION 10	0.04	5.2	1.8	0.04	100	0.07	x	x	x	x	x
CONDITION 11	0.04	5.2	1.8	0.03	90	0.07	x	x	x	x	x
CONDITION 12	0.04	5.2	1.8	0.02	80	0.07	x	x	x	x	x
CONDITION 13	0.03	5.2	1.8	0.07	140	0.05	x	x	x	x	x
CONDITION 14	0.03	5.2	1.8	0.06	130	0.05	x	x	x	x	x
CONDITION 15	0.03	5.2	1.8	0.05	120	0.05	x	x	x	x	x
CONDITION 16	0.03	5.2	1.8	0.04	100	0.05	x	x	x	x	x
CONDITION 17	0.03	5.2	1.8	0.03	90	0.05	x	x	x	x	x
CONDITION 18	0.03	5.2	1.8	0.02	80	0.05	x	x	x	x	x
CONDITION 19	0.02	5.2	1.8	0.05	120	0.04	x	x	x	x	x
CONDITION 20	0.02	5.2	1.8	0.07	140	0.04	x	x	x	x	x
CONDITION 21	0.02	5.2	1.8	0.06	130	0.04	x	x	x	x	x
CONDITION 22	0.02	5.2	1.8	0.05	120	0.04	x	x	x	x	x
CONDITION 23	0.02	5.2	1.8	0.04	100	0.04	x	x	x	x	x
CONDITION 24	0.02	5.2	1.8	0.03	80	0.04	x	x	x	x	x
CONDITION 25	0.02	5.2	1.8	0.02	80	0.04	x	x	x	x	x

FIG. 24

CARRIER GRAIN SIZE: $25\mu\text{m}$

	$\text{f}_{\text{P}}(\text{cm})$	$\rho_{\text{C}}(\text{g/cm}^3)$	$\rho_{\text{TR}}(\text{g/cm}^3)$	$A(\text{g/cm}^2)$	APPARENT COATING RATIO M	EPX/PR	CARRIER DEPOSITION	ROUGHNESS	SOLID IMAGE DENSITY	EMISSION BACKGROUND SOUND	TONER SCATTERING
CONDITION 1	0.05	5.2	1.5	0.07	150	0.08	x			x	x
CONDITION 2	0.05	5.2	1.5	0.06	140	0.08	x			x	x
CONDITION 3	0.05	5.2	1.5	0.05	130	0.08	x			o	
CONDITION 4	0.05	5.2	1.5	0.04	120	0.08	x			o	
CONDITION 5	0.05	5.2	1.5	0.03	110	0.08	x			o	
CONDITION 6	0.05	5.2	1.5	0.02	100	0.08	x			o	
CONDITION 7	0.04	5.2	1.5	0.07	150	0.06	x			o	
CONDITION 8	0.04	5.2	1.5	0.06	140	0.06	x			o	
CONDITION 9	0.04	5.2	1.5	0.05	130	0.06	x			o	
CONDITION 10	0.04	5.2	1.5	0.04	120	0.06	x			o	
CONDITION 11	0.04	5.2	1.5	0.03	110	0.06	x			o	
CONDITION 12	0.04	5.2	1.5	0.02	100	0.06	x			o	
CONDITION 13	0.03	5.2	1.5	0.07	150	0.05	x			o	
CONDITION 14	0.03	5.2	1.5	0.06	140	0.05	x			o	
CONDITION 15	0.03	5.2	1.5	0.05	130	0.05	x			o	
CONDITION 16	0.03	5.2	1.5	0.04	120	0.05	x			o	
CONDITION 17	0.03	5.2	1.5	0.03	110	0.05	x			o	
CONDITION 18	0.03	5.2	1.5	0.02	100	0.05	x			o	
CONDITION 20	0.02	5.2	1.5	0.07	150	0.03	x			o	
CONDITION 21	0.02	5.2	1.5	0.06	140	0.03	x			o	
CONDITION 22	0.02	5.2	1.5	0.05	130	0.03	x			o	
CONDITION 23	0.02	5.2	1.5	0.04	120	0.03	x			o	
CONDITION 24	0.02	5.2	1.5	0.03	110	0.03	x			o	
CONDITION 25	0.02	6.2	1.5	0.02	100	0.03	x			o	